

Date of print: 2007-10-31

Date of last alteration: 2007-10-31 - Version: English

**DETAX**Art. -No., product name: **02764-6 acrylon<sup>®</sup> automix, base + catalyst****1 Identification of the substance / preparation and of the company / undertaking**

1.1 Identification of the substance or preparation:

1.1.1 Commercial Product Name: *acrylon<sup>®</sup> automix*

1.1.2 Use: Composite material for use in audiology.

1.2 Company / undertaking identification:

Manufacturer / distributor: DETAX GmbH &amp; Co. KG

Street / POB-No.: Carl-Zeiss-Str. 4

State / postal code / city: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

**2 Composition / information on ingredients**

2.1 Chemical characterisation (preparation): Description: Mixture of methacrylic resins with auxiliary matters and pigments.

**3 Hazards identification**

3.1 Critical hazards to man and environment: If stored and handled in accordance with standard industrial practices, no damage to health is to be expected.

**4 First aid measures**

4.1 General information: Take off immediately all contaminated clothing. Medical advice is necessary in case of symptoms evidently being due to the contact of this product with skin and eyes, or being due to the inhalation of its vapours.

4.2 After inhalation: Move to fresh air immediately and lay the victim restful down, in case of respiratory distress in a stable lateral position. Seek medical advice immediately.

4.3 After contact with the skin: Wash with plenty of water and soap. Do not use organic solvents! In case of skin irritation seek medical advice.

4.4 After contact with the eyes: Rinse the open eyes immediately with plenty of water for at least 15 minutes, seek immediately medical advice.

4.5 After swallowing: Seek medical advice immediately. Rinse mouth well with water and drink plenty of water. Do not induce vomiting!

**5 Fire fighting measures**

5.1 Suitable extinguishing media: Water mist, dry powder, foam, carbon dioxide.

5.2 Extinguishing media, which must not be used for safety reasons: Water jet.

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Do not breathe resulting gases.

5.4 Special protective equipment for fire fighting: Use respiratory protection independent of recirculated air. Wear suitable protective clothing. Accomplish decontamination by means of explosion-proofed equipment.

**6 Accidental release measures**

6.1 Personal precautions: Avoid exposure. Wear suitable protective clothing. Provide for sufficient ventilation.

6.2 Environmental precautions: Observe local byelaws. Keep away from sewage treatment plants, in-shore waters and earth.

6.3 Methods for cleaning up: Absorb mechanically or with liquid binding material (sand, diatomaceous earth) and dispose of according to regulations.

Date of print: 2007-10-31

Date of last alteration: 2007-10-31 - Version: English

**DETAX**Art. -No., product name: **02764-6 acrylon® automix, base + catalyst****7 Handling and storage**

## 7.1 Handling:

Precautions for safe handling: Avoid contact of unpolymerised product with eyes, skin and clothing.

Precautions against fire and explosion: Take precautionary measures against static discharges. Cool endangered containers with water. Do not breathe combustion gases.

## 7.2 Storage:

Conditions for storage rooms and vessels: Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep container always tightly closed.

Advice for storage of incompatible materials: Keep away from oxidising agents, alkaline or acid substances.

Further information for storage: Keep in a refrigerator at  $10^{\circ} \pm 2^{\circ} \text{C} / 50^{\circ} \pm 3.6^{\circ} \text{F}$ .**8 Exposure controls / personal protection**

## 8.1 Further information for system design and engineering measures:

Provide for sufficient ventilation/suction system.

8.2 Associate substance with specific control parameters such as limit values: No associated substances.

## 8.3 Personal protection equipment:

General protection and hygiene measures: Avoid contact with eyes and skin. Take off immediately all contaminated clothing. Do not breathe vapours.

Respiratory protection (filter A): Necessary in case of insufficient ventilation, liberation of vapours due to overheating.

Hand protection: Protective gloves of butyl rubber (0.5 mm) are recommended.

Eye protection: Wear protective glasses.

**9 Physical and chemical properties**

## 9.1 Appearance:

Form: paste

Colour: base: transparent, rose-transparent, beige • catalyst: whitish

Odour: almost odourless

## 9.2 Safety parameters:

		Method (67 / 548 / EC)
Flash point .....	= > 100 °C / 212 °F	DIN 51755
Inflammability .....	not available	
Ignition temperature .....	not available	DIN 51794
Autoflammability .....	not available	
Oxidising properties .....	not available	
Explosive properties .....	not available	
Explosion limits .....	not available	
Vapour pressure .....	= < 1 hPa at 20 °C / 68 °F	
Density .....	= approx. 1.1 g/cm <sup>3</sup> at 20 °C/68 °F	DIN 51757
Solubility in water .....	= virtually insoluble	
pH-value .....	n.a.	
Distribution coefficient octanol / water:	not available	

## 9.3 Further information:

Thermal decomposition .....

not available

**10 Stability and reactivity**

10.1 Conditions to avoid:

The product is heat-sensitive, therefore keep it in a refrigerator at  $10^{\circ} \pm 2^{\circ} \text{C} / 50^{\circ} \pm 3.6^{\circ} \text{F}$ .

10.2 Materials to avoid:

Reducing agents, free-radical producing initiators, heavy metal ions.

Date of print: 2007-10-31

Date of last alteration: 2007-10-31 - Version: English

**DETAX**Art. -No., product name: **02764-6 acrylon® automix, base + catalyst**

10.3 Hazardous decomposition products: None, if handled in appropriate manner. In case of fire acrid acrylic fumes could occur.

**11 Toxicological information**

11.0 General information: Prolonged exposure or larger amounts of the product may irritate the eyes, the skin and the mucous membranes. In persons bearing a special disposition, the product may cause allergic reactions by skin contact.

## 11.1 Acute toxicity:

Acute oral toxicity (LD<sub>50</sub>): species rat > 5 000 mg/kg  
origin: literature  
these data refer to the methacrylate components.

Acute cutaneous toxicity (LC<sub>50</sub>): species rabbit > 3 000 mg/kg  
origin: literature  
these data refer to the methacrylate components.

**12 Ecological information**

12.1 Information on elimination (persistence and degradability):  
No data known.

12.2 Behaviour in environmental compartments: No data known.

12.3 Ecotoxicological effects:  
Effects in sewage treatment plants (bacteria toxicity: respiration-/reproduction inhibition):  
Do not introduce into purification plants.

12.4 Further ecological information: Do not lead into wastewater. Do not introduce into in-shore waters and earth.

**13 Disposal considerations**

13.1 Material: Recommendation: Dispose of according to regulations by incineration in a special waste incinerator.  
Observe the local byelaws.

European Waste Catalogue Ref.No.: 07 02 13 (AVV).

13.2 Contaminated packaging: Recommendation: Fully empty containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/national byelaws.

**14 Transportation information**

14.1 Land transportation ADR/RDI and GGVS/GGVE:  
GGVS/GGVE-class..... : Non-hazardous material  
ADR/RID-class..... : Non-hazardous material  
Transportation emergency card number:  
Warning board - Hazard No.:  
Nomenclature..... :  
Further information..... :  
Limited Quantities ..... :

14.2 Inland navigation ADN/ADNR:  
Further information: Non-hazardous material

14.3 Transportation by sea IMDG/GGVsea:  
IMDG/GGVsea-class .. : Non-hazardous material  
EmS-No..... :  
Marine pollutant ..... :  
Proper shipping name.. :  
Technical name..... :  
LTD. QTY..... :

Date of print: 2007-10-31

Date of last alteration: 2007-10-31 - Version: English

**DETAX**Art. -No., product name: **02764-6 acrylon® automix, base + catalyst****14.4** Air transportation ICAO-TI and IATA-DGR transportation by air:

ICAO/IATA-class..... : Non-hazardous material

Proper shipping name.. :

Technical name..... :

Further information:

Air mail transportation ..: permitted

**15 Regulatory information****15.1** Identification according to EC directives:

According to the Regulations for Hazardous Goods and the corresponding EC-Guidelines the product is not to be labelled.

**15.2** National regulations (Germany):

Classification of possible adverse effects in the aquatic environment (Wassergefährdungsklasse):

Class 1 (slight adverse effects in the aquatic environment).

Classification according to VbF: n.a.

**16 Other information**

n.a. = not applicable

n.s. = not subject to

The above information describes exclusively the safety requirements of the product(s) and is based on our present-day knowledge. It does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations.